

## Wavelength Router, also referred to as Wavelength Routing Element™ or WRE

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 1

## The Opportunity

- DWDM optical transport networks require wavelength-selective switching functions to provide network management for wavelength-based service provisioning, bandwidth management, optical-layer protection and restoration.
  - OADM, WSXC and protection switches
- No integrated all-optical solutions exist yet
- We can be the first to offer integrated all-optical dynamic wavelength routing


Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 2

## Everybody Else's Solution

1. De-multiplex the DWDM stream into individual wavelengths on separate fibers
2. Switch the optical fibers electronically or optically (OXC, FXC)
3. Re-multiplex all the fibers into DWDM.

Complex and Expensive!

## OADM Conventional Solution




Cost = \$3,000 per  $\lambda$

**COPY**

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 3

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 4

## WSXC Conventional Solution



Cost = \$3,000-\$5,000 per  $\lambda$  per fiber

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 5

## An Alternative Approach


- Network Photonics has a novel solution:

### Wavelength Routing Element™

*All-optical wavelength routing component which enables networking functions by directly switching wavelengths instead of switching fibers.*

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 6

## Wavelength Routing Element™




*Any wavelength to any output*

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 7

## Wavelength Routing Element™

it works in both directions



*Any wavelength from any input*


Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 8

**COPY**


## A Building Block

- The WRE is a building block for many optical layer applications:
  - Optical Add-Drop Multiplexer
  - Wavelength-Selective Cross-connect
  - Wavelength-Selective Protection Switching
  - Wavelength Distribution Router


## WRE Configurations: Optical Add/Drop Multiplexer (OADM)



## WRE Configurations: Wavelength-Selective Cross-Connect



## WRE Configurations: BLSR Protection Switching



**COPY**

## WRE Technology Overview

- 2 parts working in combination:
  - Dispersion-Free Spectrometer (DFS)
  - Micro-optic Routing Array (MRA)
- DFS performs spatial conversion of multiplexed wavelengths
- MRA performs switching/routing functions

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 13

## DFS Overview

- DFS is the heart of the WRE
  - a single design for dynamic and passive WREs
- Requires only one optical element both for wavelength separation and recombination
- Based on free-space diffractive optics
  - unique light path eliminates chromatic dispersion
- no electronics or moving parts


Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 14

## MRA Overview

- Implemented as an array of micro-optic retroreflectors
- Performs either dynamic or static routing
  - dynamic design uses electronic actuation
  - static design requires no power
- Non-blocking and latching

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 15

## DFS Light Path



(Not To Scale)

**COPY**


Appendix to Application of Robert T. Weverka et al. for Wavelength Router

## Dynamic MRA Implementation

- MEMS tilting micromirror array
  - proprietary design
  - one switching mirror per  $\lambda$  fabricated on a 5 mm x 50 mm silicon substrate
  - requires only  $\pm 10^\circ$  mirror tilt
- ♦ can use Texas Instruments DMD technology
- ♦ CMOS semiconductor fab process


Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 17

## MEMS Tilting MicroMirror Design



Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 18


## WRE Switching



Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 19

## Directly Switching Wavelengths


### RetroReflector Array Front View



Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 20

**COPY**

## Trapezoidal Passbands Superior Optical Performance



- 50 GHz channel spacing
- uniform gain characteristic across all channels
- low insertion loss - 3dB
- low crosstalk and high SNR - 40dB

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 21

## Dynamic WRE

- Dynamically-reconfigurable routing
- 250  $\mu$ sec switching time
- Latching
  - retains configuration with power off
- Scales to higher or lower DWDM channel densities

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 22

## Passive WRE

- Static MRA is fabricated on a silicon chip using gray-scale photolithography
  - no electronics or moving parts
  - proprietary design for 3-D retroreflector array
  - low-cost volume-fabrication process
  - same DFS as DWRE

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 23


## WRE Value Proposition

- Integrated subsystem functionality
  - simpler system design
  - ♦ no need to de-mux & re-mux
  - ♦ far fewer switching elements
  - ♦ far fewer fiber connections
- Lower system cost
  - less than \_ the cost of alternatives
- Superior optical performance
- Higher system reliability

Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 24


**COPY**

## Network Applications: Network Interconnect




Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 25

## Network Applications: 2-f BLSR Restoration




Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 27

## Network Applications: Undersea Passive OADM



Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 26

## Network Applications: FTTx Distribution Router



Appendix to Application of Robert T. Weverka et al. for Wavelength Router — Page 28

**COPY**

Document comparison done by DeltaView on Monday, December 08, 2003 2:32:12 PM

<b>Input:</b>	
Document 1	file:///H:/PTS/19930-1.DOC
Document 2	file:///H:/PTS/19930-1-3 Sub Spec for Div.DOC
Rendering set	Standard

<b>Legend:</b>	
<u>Insertion</u>	
<u>Deletion</u>	
<u>Moved from</u>	
<u>Moved to</u>	
Style change	
Format change	
Moved deletion	
Inserted cell	
Deleted cell	
Moved cell	
Split/Merged cell	
Padding cell	

<b>Statistics:</b>	
	Count
Insertions	140
Deletions	43
Moved from	1
Moved to	1
Style change	0
Format changed	0
Total changes	185